

# PecoBead 902™

## Poly Beads - Fine, Coarse, Premium

Oil & Gas Drilling Fluids / OBM & WBM



**PecoBead 902™** is an environmentally safe lubricant for drilling fluids. These beads blend into any system providing a non-abrasive insoluble lubricant that reduces torque and drag.

### PROPERTIES, TYPICAL

Appearance..... Colorless to White  
Crush strength, psi..... 10,000 +  
Vapor Density..... 0  
Specific gravity, g/cc..... 1.04  
Temperature Stability, °F..... 380°

*\*No deformation or sticking together after 30 minutes static temperature @ 380°F*

### ADVANTAGES

- Reduces torque and drag
- Helps prevent “gumbo” balling of the bit
- Prevents sticking
- Reduces pipe wear in horizontal drilling
- Acts as a seepage control agent
- Helps in running logging tools to bottom
- Economical and easily mixed into any mud system
- Environmentally safe

### SCREEN ANALYSIS, TYPICAL % RETAINED

U.S. Mesh	10	20	30	40	60	80	100
PecoBead 902™ Fine	-	-	-	0 - 5	30 - 70	25 - 50	0 - 10
PecoBead 902™ Coarse	-	-	10 - 90	5 - 80	0 - 30	0 - 8	-
PecoBead 902™ Premium	trace	0.1 - 9	25 - 34	19 - 34	21 - 46	0.0 - 0.2	trace

### TREATMENT RATE, TYPICAL

Reduce torque & drag, ppb	Initial: 2, increase to 8
Seepage control, ppb	2-4 (as needed)
Control gumbo bit- balling, ppb	1
Logging, ppb	4 (initial)

### PACKAGING

50 Lbs Bags (40 Bags / Pallet)

The information contained on this page is correct to the best of our knowledge, but is intended only as a source of information. The recommendations or suggestions herein are made without guarantee or representation as to results, and we suggest that you evaluate the recommendation contained on this page in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.