

Pecothin-100™

Invert Mud Thinner/Conditioner

Oil & Gas Drilling Fluids / OBM



Pecothin 100™ is a product designed to reduce the yield point in diesel invert emulsions. This product is active and it is designed to actively disperse solids weighted up to 18.5lb/bbl.

BENEFITS AND USE

- Reduces Yield Point and Gel Strengths.
- It can achieve up to 50% of Yield point Reduction
- Disperses solids in the mud without the need for dilution.
- Does not require changing the oil/water ratio

PHYSICAL PROPERTIES

Form & Appearance.....Dark Amber /viscous liquid
Specific gravity @ 25°C.....0.98 (8.2 lb/gal)
Flash point °F> 200°

MIXING RECOMMENDATIONS

Depending on the properties desired and solids concentration, add **Pecothin-100™** slowly to the system at a rate of 1-2 lb/bbl. Be sure that the product is added after one complete circulation so we can insure even distribution of the treatment.

SAFETY AND HANDLING

Not classified as hazardous material. Please refer to current Material Safety Data Sheet which is available upon request. This product might be toxic to aquatic animals.

PACKAGING

- 55 gal Drums
- 275 gal Totes
- Bulk

The information contained on this page is correct to the best of our knowledge, but is intended only as a source of information. The recommendations or suggestions herein are made without guarantee or representation as to results, and we suggest that you evaluate the recommendation contained on this page in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.