

PecoThin 804™

Thinner

Oil & Gas Drilling Fluids / WBM



PecoThin 804™ is a chrome-free, proprietary blended, tannin-based rheology control additive for use in water-based drilling fluids.

PROPERTIES, TYPICAL

Appearance..... Brown to Reddish-Brown Powder

PERFORMANCE PROPERTIES

Freshwater Mud			
	Base Mud	Product A	PecoThin 804™
YP, lb/100 sq ft	38	36	36
10 min gel	27	65	30
Gypsum Contaminated Mud			
	Base Mud	Product A	PecoThin 804™
YP, lb/100 sq ft	73	20	4
10 min gel	242	109	56
Lime Mud			
	Base Mud	Product A	PecoThin 804™
YP, lb/100 sq ft	300	0	0
10 min gel	300	11	2
Seawater			
	Base Mud	Product A	PecoThin 804™
YP, lb/100 sq ft	300	17	0
10 min gel	300	33	32

PACKAGING

25 lbs bag (80 bags / pallet)

The information contained on this page is correct to the best of our knowledge, but is intended only as a source of information. The recommendations or suggestions herein are made without guarantee or representation as to results, and we suggest that you evaluate the recommendation contained on this page in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

P.O. Box 431, Wharton, Texas 77488 / [phone \(979\) 531-1100](tel:9795311100) / [fax \(979\) 531-8030](tel:9795318030) / www.primeecogroup.com

