

# PEG-508™

## Sulfonated Asphalt Blend

Oil & Gas Drilling Fluids / WBM



**PEG-508™ Sulfonated Asphalt Blend** is a proprietary blended water soluble additive that stabilizes shale formations, aids in API fluid loss control, and lowers HTHP fluid loss in water based drilling fluids.

### PROPERTIES, TYPICAL

Appearance..... Dark Brown to Black Powder

Specific Gravity, g/cc ..... 1.2 – 1.5

Solubility in DI Water, % ..... 75 Minimum

### PERFORMANCE DATA @ 5 PPB

	Fann 600	Fann 300	Fann 200	Fann 100	Fann 6	Fann 3
Base Mud	112	61	43	23	2.5	1.5
<b>PEG-508™</b>	<b>111</b>	<b>60</b>	<b>41</b>	<b>22</b>	<b>2.5</b>	<b>2.0</b>
	PV	YP	10 sec Gel Strength	10 min Gel Strength	API filtrate, ml	HPHT filtrate, ml @ 275°F
Base Mud	51	10	3	3	6.4	22.4
<b>PEG-508™</b>	<b>51</b>	<b>9</b>	<b>3</b>	<b>3</b>	<b>5.0</b>	<b>17.2</b>

### PACKAGING

50 lbs bag (50 bags / pallet)

The information contained on this page is correct to the best of our knowledge, but is intended only as a source of information. The recommendations or suggestions herein are made without guarantee or representation as to results, and we suggest that you evaluate the recommendation contained on this page in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

P.O. Box 431, Wharton, Texas 77488 / [phone \(979\) 531-1100](tel:979-531-1100) / [fax \(979\) 531-8030](tel:979-531-8030) / [www.primeecogroup.com](http://www.primeecogroup.com)

