

PecoFlake 303™

Calcium Carbonate (Flakes)

Oil & Gas Drilling Fluids / OBM & WBM



PecoFlake 303™ is a unique proprietary flaked calcium carbonate effective in controlling seepage and circulation losses in completion and drilling fluids. It is available in Fine, Medium and Coarse grades.

PHYSICAL PROPERTIES

Appearance..... White Flakes
Acid Solubility, %..... 98 – 99.5
Hygroscopic No

SCREEN ANALYSIS, TYPICAL % RETAINED

U.S. Mesh	4	8	12	16	20	25	30	60	100	200
PecoFlake 303 - Fine	0	0	0	0	0	0	1.5	36.4	35.8	17.7
PecoFlake 303 - Medium	0	0	0	0	24.0	0	0	29.0	41.0	0
PecoFlake 303 - Coarse	0	39.1	27.9	33.0						

PACKAGING

50 Lbs Bags (40 Bags / Pallet)

The information contained on this page is correct to the best of our knowledge, but is intended only as a source of information. The recommendations or suggestions herein are made without guarantee or representation as to results, and we suggest that you evaluate the recommendation contained on this page in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.